

MSDS CODE: BL4

Page 1 of 5

Date Revised: 01/17/2003

Date Printed: 5/21/2003

Prepared By: Nick Paris

Reason for Revision: See Section 16

(1) CHEMICAL, PRODUCT AND COMPANY IDENTIFICATION:

Product Code: 641, 677, 679, 6058, 6059, 6069, 6114, 6130, 6145, 6156, 6455, 6522, 6804, 6997, 61002, 61041, 61078, 61117, 61205, 61222, 61250, 6863

Product Name: Iron Oxide Brown/Tan

Chemical Family: Inorganic Metal Oxide

Synonyms: Synthetic Iron Oxide

C.A.S. Number: Mixture 1309-37-1+51274-00-1+1317-61-9

Color Index Name: Pigment Brown 6

Color Index Number: 77492

DCMA Number: Not Available

Manufacturer's Name/Address:

Rockwood Pigments/Davis Colors, 7011 Muirkirk Road, Beltsville, Maryland, USA 20705

Business Tel: (301) 210-7800 9a-5p (0900-1700) EST M-F

Rockwood Pigments/Davis Colors, 3700 E. Olympic Blvd., Los Angeles, California, USA

90023 Business Tel: (323) 269-7311 9am-5pm (0900-1700) PST M-F

24 Hour Emergency (CHEMTREC): 800-424-9300

(2) COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Hazardous Ingredients (29CFR1910.1200):

Components:	C.A.S.	%	Exposure Limits (8 Hrs.TWA)	
			OSHA PEL	ACGIH TLV
Silicon Dioxide	7631-86-9	(<4)	6 mg/m3	10 mg/m3
Iron Oxide (fume*)		(none)	10 mg/m3	5 mg/m3*
Iron Oxide (red)	1309-37-1	(10-90%)	Not Est.	Not Est.

*5 mg/m3 dust as Fe. These limits are for Iron Oxide FUME. A FUME is defined as an "aerosol of solid particles produced by condensation of vaporized iron metal", such as may occur during welding. In normal use, iron oxide pigments are not present in the form of a FUME.

Non-Hazardous Ingredients:

Components:	C.A.S.	%	Exposure Limits (8 Hrs.TWA)	
			OSHA PEL	ACGIH TLV
Iron Oxide (yellow)	51274-00-1	(0-75%)	Not Est.	Not Est.
Iron Oxide (Black)	1317-61-9	(5-40%)	Not Est.	Not Est.

(3) HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****

Dry, brown or gold powder with little to no odor. Will not burn or react. Long term inhalation can cause lung irritation or siderosis. Packaging can burn in fire, releasing toxic gases or fumes.

HMIS Codes: H=0, F=0, R=1, P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

Potential Health Effects:

Eyes: Non-irritating to the eyes. Excessive exposure to airborne dust may reduce visibility and/or cause unpleasant deposits.

Skin: Will not irritate skin and is not likely to cause allergic skin reaction. Injury to the skin or mucus membranes can occur by direct mechanical action or by rigorous skin cleaning necessary for removal of dust.

Ingestion: Small amounts (a tablespoonful) swallowed are not likely to cause injury. Not a hazard in normal industrial use.

Inhalation: Not a hazard in normal industrial use. Wear respirator and avoid breathing dust. As with all dusty materials, inhalation may cause respiratory irritation,

sneezing, coughing and runny nose.

Human Effects and symptoms of overexposure:

Acute: To date, adverse health effects from exposure have not been reported among workers using this pigment. On the basis of Animal Toxicity Data (see Section 11), we would expect this product to be non-irritating to the eyes and skin and essentially non-toxic by ingestion. However, excessive exposure to airborne dust may reduce visibility and/or cause unpleasant deposits in the eyes, ears and nose. Injury to the skin or mucous membranes can occur by direct mechanical action or by rigorous skin cleaning necessary for removal of dust.

Chronic: Prolonged inhalation of amorphous silica may produce x-ray changes in the lungs without disability.

Other Effects: No chronic effects are known from repeated exposure to iron oxide PIGMENT. Prolonged inhalation (6 to 10 years) of iron oxide FUME has been reported to produce changes in lung x-rays of exposed individuals. This condition, siderosis, is considered to be benign pneumoconiosis that exhibits no adverse health effects. Siderosis has been observed among occupations such as arc-welders where iron oxide FUMES are present. To the best of our knowledge, this condition has not been observed after prolonged exposure to iron oxide pigment. There is no Iron Oxide FUME contained in this product and none should be generated under normal use.

Medical Conditions Aggravated by Exposure: None known

Carcinogenicity: IARC: Not Listed NTP: Not Listed OSHA: Not Regulated

Other: IARC and NTP both contain listings for underground hematite mining. These listings are for the occupational exposures associated with the mining process which include radon, a known lung carcinogen. NIOSH in the Registry of Toxic Effects of Chemical Substances (RTECS) lists Iron Oxide as a suspect human carcinogen. However, the IARC reference to underground hematite mining is the source for this classification. Based on information currently available, this product is not considered a carcinogen.

(4) FIRST AID MEASURES

Eyes: Immediately flush eyes with plenty of water. Remove contact lenses. Continue flushing. Consult a physician if irritation persists.

Skin: Wash with soap and water. Wash clothing before re-use. Get medical attention in the unlikely event that irritation develops or persists.

Ingestion: Swallowing less than an ounce will not cause harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and contact medical personnel or poison control center. Do not give anything by mouth to an unconscious person.

Inhalation: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dust or fumes, move from dusty area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

(5) FIRE FIGHTING MEASURES

Flammable Properties: Not Flammable.

Flash Point: Will not Flash.

Upper Explosive Limit (UEL): Will not explode

Lower Explosive Limit (LEL): Will not explode

Auto-ignition Temperature: Exposure to excessive heat greater than 176F (80C) can cause the portion of Iron Oxide Black contained in this product to slowly auto-oxidize which generates additional heat. Under certain conditions, this heat may be sufficient to cause the bag or combustible materials stored nearby to ignite.

Extinguishing Media: This product is not combustible or flammable. Use extinguishing agents that are suitable to the surrounding fire; water spray, dry chemical, foam or CO2

Fire fighting Instructions: Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes and smoke inhalation.

(6) ACCIDENTAL RELEASE MEASURES

Small Spill: If dust is generated, use appropriate respiratory protection. Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust.

Large Spill: Use recommended protective clothing and respiratory protection. Use shovel to reclaim material. Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust. Spill area can be washed with water. Collect wash water for approved disposal. Prevent runoff from entering storm sewers and ditches which lead to natural waterways.

(7) HANDLING AND STORAGE

Storage: Store dry at ambient temperature away from food and beverages, excessive heat or flame sources (furnace, kilns, boilers etc.). Avoid breathing dust. Avoid contact with eyes and skin. Wash thoroughly after handling.

Handling: Avoid prolonged or repeated breathing of dust. Avoid getting in eyes or on skin. Wash thoroughly after handling. Avoid contact with moisture. Re-seal bag immediately after use. Pallets are wrapped in polyethylene plastic. Removal may cause an electrostatic spark; therefore removal of the wrap should not be in the presence of flammable vapors.

Storage Temperature (Min/Max)...:Ambient/50C (122F)

Shelf Life.....:Unlimited in closed container

Special Sensitivity.....:Excessive Heat

Other Precautions.....:None

(8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Maintain air levels below the recommended exposure limit using exhaust ventilation if necessary.

Eyes: Safety Glasses.

Skin: Body-covering clothing. Rubber, Plastic, Leather or cloth gloves are suggested to facilitate personal hygiene.

Respiratory Protection: Work ambient dust concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved respirator with dust prefilter should be worn.

Other: Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous chemicals.

Work/Hygiene Practices: Employees should wash their hands and face before eating, drinking or using tobacco products.

(9) PHYSICAL AND CHEMICAL PROPERTIES

Appearance.....:Solid Brown or Gold Powder

Odor.....:Odorless

Physical State.....:Dry Powder

pH.....:5 - 9 in 50 g/l H₂O aqueous suspension; DIN 787/9

Vapor Pressure.....:Not a vapor

Vapor Density.....:Not a vapor

Boiling Point.....:Not Applicable

Freezing Point.....:Not Applicable

Melting Point.....:Greater than 1000C (1832F)

Solubility in Water.....:Insoluble

Specific Gravity (g/ml).....:4.4 to 5.0 @ 20C (68F); DIN 787/10

Bulk Density (kg/m³).....:500 to 1100 @ 20C (68F)

Particle Size (microns).....:0.3-0.6

Volatile Organic Compounds (VOC):None

MATERIAL SAFETY DATA SHEET

MSDS CODE: BL4

Date Revised: 01/17/2003

Prepared By: Nick Paris

Page 4 of 5

Date Printed: 5/21/2003

Reason for Revision: See Section 16

Chemical Formula.....: $\text{Fe}_3\text{O}_4 + \text{Fe}_2\text{O}_3 + \text{FeOOH}$

(10) STABILITY AND REACTIVITY

Chemical Stability (Conditions to Avoid): Stable. Keep away from flames and heat. Exposure to excessive heat greater than 176F (80C) can cause the portion of Iron Oxide Black contained in this product to slowly auto-oxidize which generates additional heat. Under certain conditions, this heat may be sufficient to cause the bag or combustible materials stored nearby to ignite.

Incompatibility (materials to avoid): No known material incompatibilities

Decomposition Temperature F(C): Does not Decompose

Hazardous Decomposition Products: None

Hazardous Polymerization: Will not occur

(11) TOXICOLOGICAL INFORMATION

Eyes: Not irritating to rabbit eyes

Skin: Not irritating to rabbit skin Dermal, LD 50 not established for product

Ingestion: Non irritating. The oral, LD50 for rats is greater than 5000 mg/L

Inhalation: Non irritating. LC 50 not established for product

Subchronic: Data not established for product

Chronic/Carcinogenicity: Data not established for product

Other (Mutagenic, Teratogenic, Reproductive Tests): The IARC monograph on underground hematite mining (1972) states, "No carcinogenic effects were observed in mice, hamsters, or guinea pigs given ferric oxide intratracheally."

(12) ECOLOGICAL INFORMATION

Ecotoxicological Information: Fish toxicity: Golden Orfe (*Leuciscus idus*) LCo greater than 1000 mg/L

Chemical Fate Information: No appreciable bioconcentration is expected in the environment.

(13) DISPOSAL CONSIDERATIONS

Material which cannot be re-used should be disposed in accordance with federal, state and local environmental control regulations at an authorized site. This product when discarded as sold is not a RCRA hazardous waste. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40CFR 261.20-24)

(14) TRANSPORT INFORMATION

DOT Shipping Name: None

Technical Shipping Name: Inorganic Oxide

DOT Hazardous Classification: Non-Regulated

DOT Hazard Class: Non-Regulated

DOT Identification Number: None

DOT Labels required: None

DOT Placards required: None

UN Class: None

UN/NA Number: None

Freight Class: Iron Oxide; NOI

(15) REGULATORY INFORMATION

=====U.S. Federal Regulations=====

OSHA: This product is considered Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200) due to potential to auto-oxidize (self-heat). See section 5.

CERCLA/SUPERFUND: (40 CFR 117,302) Reportable Quantity (RQ): Not Reportable, however, we recommend you contact local authorities to verify requirements for your site.

MATERIAL SAFETY DATA SHEET

MSDS CODE: BL4

Date Revised: 01/17/2003

Prepared By: Nick Paris

Page 5 of 5

Date Printed: 5/21/2003

Reason for Revision: See Section 16

Superfund Amendments and Reauthorization Act (SARA), Title III:

Section 302 (Extremely Hazardous Substances): None

Section 311/312 (Hazard Categories): Delayed Health Hazard

Section 313 (Reportable Toxic Ingredients):

Chemical Name: C.A.S. Concentration

None Reportable

T.S.C.A.: This product is listed on TSCA Inventory.

=====International Regulations=====

Canadian WHMIS: Not restricted/non-hazardous

Canadian Environmental Protection Act (CEPA): All components of this product are on the Domestic Substances List (DSL), and acceptable for use under the provisions of CEPA.

EINECS: All components of this product are on the European Inventory of Existing Commercial Chemical Substances.

=====State Regulations=====

California Proposition 65 Warning: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Chemical Name:	C.A.S.	Concentration	State Code
Iron Oxide Red	1309-37-1	10 to 90%	PA3, NJ4
Iron Oxide Yellow	51274-00-1	0 to 75%	PA3, NJ4
Iron Oxide Black	1317-61-9	0 to 40%	PA3, NJ4
Silicon Dioxide (Amorphous)	7631-86-9	2 to 4%	PA3, MA, NJ4
Arsenic	7440-38-2	<100 ppm	CA, MA
Cadmium	7440-43-9	<5 ppm	CA, MA
Mercury	7439-97-6	<1 ppm	CA
Nickel	7440-02-0	<400 ppm	CA, MA
Lead	7439-92-1	<100 ppm	CA, MA
Aniline	62-53-3	<1 ppm	CA

Note: This information based on random sample analyses. Actual content may vary from batch to batch.

CA= Calif. Safe Drinking Water and Toxic Enforce Act (Prop.65)

MA= Massachusetts Hazardous Substance List

NJ4= New Jersey Other- included in 5 predominant ingredients >1%

PA3= Pennsylvania Non-hazardous present at 3% or greater

(16) OTHER INFORMATION

Reason for revision: New MSDS format, re-issue=1, P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the Manufacturer. The data on this sheet relates only to the specific material designated herein. It may not be valid for this material if used in combination with any other materials or process. It is the users responsibility to verify suitability and completeness of this information for their own particular use. The Manufacturer assumes no legal responsibility for use or reliance upon these data.